

Galvanized square wire mesh is made of in galvanized iron wire. Square wire mesh is commonly used at mosquito net and in sieves, sugar, chemical, stone crusher.



-		
u	Specification	available:

- 1. Gauge: BWG 15 To BWG 30
- 2. Mesh: 2 to 14
- 3. Width: 2' to 7'
- 4. Length: 10' to 300'
- 5. Workmanship: hot-dipped gal. Before or after weaving;
 Elec.Gal. Before or after weaving.

Gauge	Mesh	Wid	GW/Rell
BWG15	2	3 X100	50
BWG16	2	3.X100	40
EWGIN	- 3	EX100	43
BWG20	. 5	3'X100'	34
BWG20	-4	3 X100	45
BWG25	4	3.X100.	35.6
BW522	4	37X100	27
BWG21	-4	37X100°	22
BW622	1.5	3'X100'	34
BW621	5	3'X100'	27.6
BW524	3	TX100	21.8
BWG25	- 5	3 X100	17.4
EWG33	- 6	EX100	41.
BWG23	6	3'X100'	13
BWG24	6	3 X100	25.2
BW525	6	370100	21.
EW526	6	3.XT00.	17
BW524		EX100	34
8WG25		378100	37.8
BWG26	8	3.XT00.	22.5
8WG27		FX100	28
8WG26	10	3 X100	28
8WG27	10	37X100	25
BWG28	10	3'X100	37.5
8WG29	10	3 X100	15
EM038	10	3.X100,	53

Mesh Diameter	Tolerance (mm)	Max Deviation Tolerance (mm)
32	0.50	1.61
34	0.45	1.36
36	0.40	1.19
38	0.35	1.06
20	0.30	0.97
30	0.25	0.59
40	0.20	0.44
50	0.16	0.35
60	0.15	627